

DH150 - Hot Water Hose



Application: Conveying of hot water for cleaning equipment and cooling systems

Temperature: -35°C~+120°C

Inner tube: Black smooth heat resistant synthetic rubber

Reinforcement: High tensile cord

Cover: Black, heat, corrosion and abrasion resistant rubber compound

Part. No	Hose I.D.		Hose O.D		Max.Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	psi	psi
LH-DH150-008	5/16	8	20	0.787	100	330	10	150	30	450
LH-DH150-010	3/8	10	23	0.906	100	330				
LH-DH150-013	1/2	13	28	1.102	100	330				
LH-DH150-016	5/8	16	31	1.220	100	330				
LH-DH150-019	3/4	19	36	1.417	61	200				
LH-DH150-025	1	25	45	1.772	61	200				
LH-DH150-032	1-1/4	32	43	1.693	61	200				
LH-DH150-035	1-3/8	35	46	1.811	61	200				
LH-DH150-038	1-1/2	38	49	1.929	61	200				
LH-DH150-045	1-3/4	45	56	2.205	61	200				
LH-DH150-051	2	51	64	2.520	61	200				
LH-DH150-063	2-1/2	63	77	3.031	61	200				
LH-DH150-076	3	76	89	3.504	61	200				
LH-DH150-090	3-1/2	90	104	4.094	61	200				
LH-DH150-102	4	102	115	4.528	61	200				