

DO150 - Oil Discharge Hose



Application: Draw and delivery of fuel oil up to 30% aromatic content.

Temperature: -40°C~+100°C

Inner tube: Black smooth synthetic rubber

Reinforcement: High tensile cord

Cover: Black, ozone, oil and aging resistant rubber compound

Part. No	Hose I.D.		Hose O.D		Max. Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	bar	psi
LH-DO150-025	1	25	36	1.417	61	200	10	150	30	450
LH-DO150-032	1-1/4	32	43	1.693	61	200				
LH-DO150-038	1-3/8	35	46	1.811	61	200				
LH-DO150-045	1-1/2	38	49	1.929	61	200				
LH-DO150-051	1-3/4	45	56	2.205	61	200				
LH-DO150-063	2	5	62	2.441	61	200				
LH-DO150-076	2-1/2	63	75	2.953	61	200				
LH-DO150-080	3	76	91	3.583	61	200				
LH-DO150-090	3-3/16	80	95	3.740	61	200				
LH-DO150-102	3-1/2	90	105	4.134	61	200				
LH-DO150-127	4	102	117	4.606	61	200				
LH-DO150-152	5	127	142	5.591	30.5	100				
LH-DO150-203	6	152	167	6.575	30.5	100				
LH-DO150-203	8	203	227	8.937	15	50				