


## DW300 - Water Hose



**Application:** For transmission of water, air, inert gases and non corrosive liquid

**Temperature:** -35°C~+80°C

**Inner tube:** Black smooth synthetic rubber

**Reinforcement:** High tensile cord

**Cover:** Black, ozone, aging and abrasion resistant rubber compound

Part. No	Hose I.D.		Hose O.D		Max.Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	psi	psi
LH-DW150-032	1 1/4	32	43	1.693	61	200	20	300	60	900
LH-DW150-038	1 1/2	38	49	1.929	61	200				
LH-DW150-045	1 3/4	45	59	2.323	61	200				
LH-DW150-051	2	51	65	2.559	61	200				
LH-DW150-063	2 1/2	63	79	3.110	61	200				
LH-DW150-076	3	76	92	3.622	61	200				
LH-DW150-102	4	102	120	4.724	61	200				
LH-DW150-127	5	127	140	5.512	30.5	100				
LH-DW150-152	6	152	165	6.496	30.5	100				
LH-DW150-203	8	203	217	8.543	15	50				
LH-DW150-254	10	254	281	11.063	15	50				
LH-DW150-304	12	304	333	13.110	15	50				