

# SS150 Slurry Suction and Discharge Hose

## SP600 Slurry Delivery Hose

## SS150 - Slurry Suction and Discharge Hose



**Application:** For suction and delivery of slurry and high abrasive materials

**Temperature:** -40°C~+85°C

**Inner tube:** Super abrasion resistant natural rubber

**Reinforcement:** High tensile cord and helix steel wire

**Cover:** Super abrasion resistant natural compound

Part. No	Hose I.D.		Hose O.D		Max.Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	psi	psi
LH-SS150-152	6	152	184	7.244	30.5	100	10	150	30	450
LH-SS150-203	8	203	235	9.252	15	50				
LH-SS150-254	10	254	286	11.260	15	50				
LH-SS150-305	12	305	344	13.543	15	50				

## SP600 - Slurry Delivery Hose



**Application:** Delivery of slurry and high abrasive materials

**Temperature:** -40°C~+85°C

**Inner tube:** Black abrasion rubber compound

**Reinforcement:** High tensile cord

**Cover:** Black, high abrasion rubber compound

Part. No	Hose I.D.		Hose O.D		Max.Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	psi	psi
LH-SP600-032	1-1/4	32	45	1.811	61	200	40	600	120	1800
LH-SP600-038	1-1/2	38	54	2.126	61	200				
LH-SP600-051	2	51	68	2.677	61	200				
LH-SP600-063	2-1/2	63	83	3.268	61	200				
LH-SP600-076	3	76	98	3.858	61	200				
LH-SP600-102	4	102	130	5.118	61	200				