

## Tak150 - Tank Truck Hose



**Application:** Draw and delivery of petroleum based products up to 50% aromatic content.



**Temperature:** -40°C~+100°C

**Inner tube:** Black smooth synthetic rubber

**Reinforcement:** High tensile cord and helix steel wire

**Cover:** Black, ozone, oil and aging resistant rubber compound

Part. No	Hose I.D.		Hose O.D		Max. Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	bar	psi
LH-TAK150-025	1	25	37	1.457	61	200	10	150	30	450
LH-TAK150-032	1-1/4	32	44	1.732	61	200				
LH-TAK150-038	1-1/2	38	50	1.969	61	200				
LH-TAK150-051	2	51	64	2.520	61	200				
LH-TAK150-063	2-1/2	63	77	3.031	61	200				
LH-TAK150-076	3	76	91	3.583	61	200				
LH-TAK150-102	4	102	119	4.685	61	200				
LH-TAK150-152	6	152	171	6.732	30.5	100				
LH-TAK150-203	8	203	228	8.976	15	50				



## Tak300 - Tank Truck Hose

Part. No	Hose I.D		Hose O.D		Max.Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	bar	psi
LH-TAK300-025	1	25	36	1.417	61	200	20	300	60	900
LH-TAK300-032	1-1/4	32	44	1.732	61	200				
LH-TAK300-038	1-1/2	38	51	2.008	61	200				
LH-TAK300-051	2	51	65	2.559	61	200				
LH-TAK300-063	2-1/2	63	80	3.150	61	200				
LH-TAK300-076	3	76	93	3.661	61	200				
LH-TAK300-102	4	102	120	4.724	61	200				
LH-TAK300-152	6	152	175	6.890	30.5	100				