

PVC Layflat Discharge Hose



Application: Applied to convey liquid materials in industry, agriculture irrigation, mines engineering.

Temperature: 10°C~60°C

Feature:

- Two step extrusion products.
- Soft surface, good flexibility and attractive appearance.
- Long service life and qualified PVC synthesis.
- Non-toxic, flavorless and environmental protection.

Part Number	Type	Working pressure	Weight	Length
LIGHT DUTY	Inch	bar	Kg/m	M
L-OLPDH100	1"	4	0.20	100
L-OLPDH150	1-1/2"	4	0.27	100
L-OLPDH200	2"	4	0.33	100
L-OLPDH250	2-1/2"	4	0.42	100
L-OLPDH300	3"	4	0.56	100
L-OLPDH400	4"	4	0.70	100
L-OLPDH500	5"	4	1.00	100
L-OLPDH600	6"	4	1.35	100
L-OLPDH800	8"	4	1.70	100
Part Number	Type	Working pressure	Weight	Length
MEDIUM DUTY	Inch	bar	Kg/m	M
L-OMPDH150	1-1/2"	6	0.30	100
L-OMPDH200	2"	6	0.36	100
L-OMPDH250	2-1/2"	6	0.49	100
L-OMPDH300	3"	6	0.62	100
L-OMPDH400	4"	6	0.80	100
L-OMPDH500	5"	6	1.15	100
L-OMPDH600	6"	6	1.55	100
L-OMPDH800	8"	6	1.95	100
Part Number	Type	Working pressure	Weight	Length
HEAVY DUTY	Inch	bar	Kg/m	M
L-OHPDH150	1-1/2"	8	0.33	100
L-OHPDH200	2"	8	0.475	100
L-OHPDH250	2-1/2"	8	0.55	100
L-OHPDH300	3"	8	0.65	100
L-OHPDH400	4"	8	0.95	100