

PVC Layflat Discharge Hose



Application: Applied to convey liquid materials in industry, agriculture irrigation, mines engineering.

Temperature: -5°C~65°C.

Feature:

- Once-molded by extruder plastic, it will be good at light weight, good flexibility, small thickness and high resistance pressure etc.
- Non-toxic, flavorless and environmental protection.
- Aging resistant, stretching resistant and anti-wrinkle.

Part Number	Type	Working pressure	Weight	Length
LIGHT DUTY	Inch	bar	Kg/m	M
L-NLPDH100	1"	4	0.15	100
L-NLPDH125	1-1/4"	4	0.17	100
L-NLPDH150	1-1/2"	4	0.19	100
L-NLPDH200	2"	4	0.22	100
L-NLPDH250	2-1/2"	4	0.30	100
L-NLPDH300	3"	4	0.36	100
L-NLPDH400	4"	4	0.55	100
L-NLPDH500	5"	4	0.75	100
L-NLPDH600	6"	4	0.90	100
L-NLPDH800	8"	4	1.60	100
L-NLPDH1000	10"	4	2.60	100
Part Number	Type	Working pressure	Weight	Length
MEDIUM DUTY	Inch	bar	Kg/m	M
L-NMPDH075	3/4"	6	0.11	100
L-NMPDH100	1"	6	0.16	100
L-NMPDH125	1-1/4"	6	0.19	100
L-NMPDH150	1-1/2"	6	0.22	100
L-NMPDH200	2"	6	0.30	100
L-NMPDH250	2-1/2"	6	0.43	100
L-NMPDH300	3"	6	0.50	100
L-NMPDH400	4"	6	0.80	100
L-NMPDH500	5"	6	1.08	100
L-NMPDH600	6"	6	1.60	100
L-NMPDH800	8"	6	2.20	100
Part Number	Type	Working pressure	Weight	Length
HEAVY DUTY	Inch	bar	Kg/m	M
L-NHPDH075	3/4"	10	0.14	50
L-NHPDH100	1"	10	0.20	50
L-NHPDH125	1-1/4"	10	0.21	50

PVC Layflat Discharge Hose

L-NHPDH150	1-1/2"	10	0.3	50
L-NHPDH175	1-3/4"	10	0.35	50
L-NHPDH200	2"	10	0.42	50
L-NHPDH250	2-1/2"	10	0.70	50
L-NHPDH300	3"	10	0.85	50
L-NHPDH400	4"	10	1.20	50
L-NHPDH600	6"	8	2.00	50
L-NHPDH800	8"	6	2.80	50