


BM150

Cement Suction and Discharge Hose

BM150 - Cement Suction and Discharge Hose



Application: Dry material suction and delivery hose used to transfer cement, sand gravel, silica and other abrasive materials.

Temperature: -40°C~+85°C

Inner tube: Black synthetic rubber, wear resistant and impact resistant.

Reinforcement: High tensile cord

Cover: Abrasion resistant rubber compound

Part. No	Hose I.D.		Hose O.D		Max.Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	psi	psi
LH-BM150-025	1	25	38	1.496	61	200	10	150	30	450
LH-BM150-032	1-1/4	32	44	1.732	61	200				
LH-BM150-038	1-1/2	38	52	2.047	61	200				
LH-BM150-051	2	51	64	2.520	61	200				
LH-BM150-063	2-1/2	63	77	3.031	61	200				
LH-BM150-076	3	76	90	3.543	61	200				
LH-BM150-102	4	102	118	4.646	61	200				
LH-BM150-127	5	127	143	5.630	30.5	100				
LH-BM150-152	6	152	170	6.693	30.5	100				
LH-BM150-203	8	203	225	8.858	15	50				
LH-BM150-254	10	254	280	11.024	15	50				

