

Multipurpose Hose



Application: Economic Hose for transmission of air, water. Suitable for low pressure painting.

Temperature: -35°C~+80°C

Inner tube: Black smooth synthetic rubber

Reinforcement: High tensile cord

Cover: Yellow, ozone and aging resistant rubber compound

Part. No	Hose I.D.		Hose O.D		Max.Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	psi	psi
LH-DA200-005	3/16	5	11.5	0.453	100	330	15	200	45	600
LH-DA200-006	1/4	6	13.5	0.531	100	330				
LH-DA200-008	5/16	8	16	0.630	100	330				
LH-DA200-010	3/8	10	17.5	0.689	100	330				
LH-DA200-013	1/2	13	21.3	0.839	100	330				
LH-DA200-016	5/8	16	25.4	1.000	100	330				
LH-DA200-019	3/4	19	28.7	1.130	61	200				
LH-DA200-025	1	25	37.3	1.469	61	200				

Part. No	Hose I.D.		Hose O.D		Max.Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	psi	psi
LH-DA300-005	3/16	5	11.5	0.453	100	330	20	300	60	900
LH-DA300-006	1/4	6	13.8	0.543	100	330				
LH-DA300-008	5/16	8	16.3	0.642	100	330				
LH-DA300-010	3/8	10	17.9	0.705	100	330				
LH-DA300-013	1/2	13	21.8	0.858	100	330				
LH-DA300-016	5/8	16	25.9	1.020	100	330				
LH-DA300-019	3/4	19	30.2	1.189	61	200				
LH-DA300-025	1	25	38.1	1.500	61	200				
LH-DA300-032	1 1/4	32	45.6	1.795	61	200				
LH-DA300-038	1 1/2	38	53.2	2.094	61	200				