

DW150 - Water Hose



Application: For transmission of water, air, inert gases and non corrosive liquid

Temperature: -35°C~+80°C

Inner tube: Black smooth synthetic rubber

Reinforcement: High tensile cord

Cover: Black, ozone, aging and abrasion resistant rubber compound

Part. No	Hose I.D.		Hose O.D		Max.Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	psi	psi
LH-DW150-032	1 1/4	32	43	1.693	61	200	10	150	30	450
LH-DW150-038	1 1/2	38	49	1.929	61	200				
LH-DW150-045	1 3/4	45	56	2.205	61	200				
LH-DW150-051	2	51	62	2.441	61	200				
LH-DW150-063	2 1/2	63	75	2.953	61	200				
LH-DW150-076	3	76	91	3.583	61	200				
LH-DW150-102	4	102	117	4.606	61	200				
LH-DW150-127	5	127	140	5.512	30.5	100				
LH-DW150-152	6	152	166	6.535	30.5	100				
LH-DW150-203	8	203	218	8.583	15	50				
LH-DW150-254	10	254	272	10.709	15	50				
LH-DW150-304	12	304	322	12.677	15	50				

