

Do300 - Oil Discharge Hose



Application: For delivery of petroleum based products up to 30% aromatic content

Temperature: -40°C~+100°C

Inner tube: High tensile cord

Reinforcement: High tensile cord

Cover: Black, ozone, oil and aging resistant rubber compound

Part. No	Hose I.D.		Hose O.D		Max. Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	bar	psi
LH-DO300-025	1	25	36	1.417	61	200	20	300	60	900
LH-DO300-032	1-1/4	32	43	1.693	61	200				
LH-DO300-035	1-3/8	35	46	1.811	61	200				
LH-DO300-038	1-1/2	38	49	1.929	61	200				
LH-DO300-045	1-3/4	45	56	2.205	61	200				
LH-DO300-051	2	51	62	2.441	61	200				
LH-DO300-063	2-1/2	63	75	2.953	61	200				
LH-DO300-076	3	76	91	3.583	61	200				
LH-DO300-080	3-3/16	80	95	3.740	61	200				
LH-DO300-090	3-1/2	90	105	4.134	61	200				
LH-DO300-102	4	102	117	4.606	61	200				
LH-DO300-127	5	127	142	5.591	30.5	100				
LH-DO300-152	6	152	167	6.575	30.5	100				

