

FH - Fuel Hose



Application: It is widely used to convey gasoline, diesel fuel, lubrication oil, or the vapor present in either the fuel system of cars, trains and vessels or in the crankcase of internal combustion engines in mobile, stationary applications.

Temperature: -34 °C~+100 °C

Inner tube: Black smooth synthetic rubber

Reinforcement: High tensile cord

Cover: Black, ozone, oil and heat resistant rubber compound

Technical standard: SAE 30R6 / SAE 30R7

Part. No	Hose I.D.		Hose O.D		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	bar	psi	bar	psi
LH-FH300-005	3/16	4.76	0.43	10.32	20	300	80	1200
LH-FH300-006	1/4	6.35	0.50	12.70	20	300	80	1200
LH-FH300-008	5/16	7.94	0.56	14.29	20	300	80	1200
LH-FH300-010	3/8	9.53	0.63	15.88	20	300	80	1200
LH-FH300-013	1/2	12.7	0.78	19.84	20	300	80	1200
LH-FH300-016	5/8	15.9	0.94	23.81	10	150	40	600
LH-FH300-019	3/4	19.1	1.13	28.58	10	150	40	600
LH-FH300-025	1	25.4	1.38	34.93	10	150	40	600