

SB150 - Sand Blast Hose



Application: Suitable for rust cleaning, delivery of abrasive material, quartz sand, iron sand, cement and mud etc.

Temperature: -20°C~+85°C

Inner tube: Black synthetic rubber, wear resistant and impact resistant.

Reinforcement: High tensile cord

Cover: Abrasion resistant rubber compound

Part. No	Hose I.D.		Hose O.D		Max.Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	psi	psi
LH-SB150-019	3/4	19	37	1.457	61	200	10	150	30	450
LH-SB150-025	1	25	41	1.614	61	200				
LH-SB150-032	1-1/4	32	49	1.929	61	200				
LH-SB150-038	1-1/2	38	62	2.441	61	200				
LH-SB150-051	2	51	74	2.913	61	200				
LH-SB150-063	2-1/2	63	88	3.465	61	200				

DC1200 - Cement Delivery Hose



Application: It is widely used to convey dry cement, sand gravel, silica and other abrasive materials.

Temperature: -40°C~+85°C

Inner tube: Black smooth synthetic rubber

Reinforcement: High tensile cord

Cover: Abrasion resistant rubber compound

Part. No	Hose I.D.		Hose O.D		Max.Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	psi	psi
LH-DC1200-051	2	51	70	2.756	61	200	85	1230	200	2900
LH-DC1200-063	2-1/2	63	88	3.465	61	200				
LH-DC1200-076	3	76	102	4.016	61	200				
LH-DC1200-102	4	102	130	5.118	61	200				
LH-DC1200-127	5	127	155	6.102	30.5	100				
LH-DC1200-152	6	152	184	7.244	30.5	100				