

SO150 - Oil Suction Hose



Application: Draw and delivery of fuel oil up to 30% aromatic content.

Temperature: -40°C~+100°C

Inner tube: Black smooth synthetic rubber

Reinforcement: High tensile cord and helix steel wire

Cover: Black, ozone, oil and aging resistant rubber compound

Part. No	Hose I.D.		Hose O.D		Max. Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	bar	psi
LH-SO150-025	1	25	38	1.496	61	200	10	150	30	450
LH-SO150-032	1-1/4	32	45	1.772	61	200				
LH-SO150-038	1-1/2	38	51	2.008	61	200				
LH-SO150-045	1-3/4	45	59	2.323	61	200				
LH-SO150-051	2	51	65	2.559	61	200				
LH-SO150-063	2-1/2	63	79	3.110	61	200				
LH-SO150-076	3	76	93	3.661	61	200				
LH-SO150-090	3-1/2	90	107	4.213	61	200				
LH-SO150-102	4	102	119	4.685	61	200				
LH-SO150-127	5	127	145	5.709	30.5	100				
LH-SO150-152	6	152	171	6.732	30.5	100				
LH-SO150-203	8	203	227	8.937	15	50				

