

SW150 - Water Suction Hose



Application: It handles sewage, waste water or non corrosive liquid etc.

Temperature: -40°C~+85°C

Inner tube: Black smooth synthetic rubber

Reinforcement: High tensile cord and helix steel wire

Cover: Black, ozone, aging and abrasion resistant rubber compound

Part. No	Hose I.D.		Hose O.D		Max.Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	psi	psi
LH-SW150-025	1	25	38	1.496	61	200	10	150	30	450
LH-SW150-032	1-1/4	32	45	1.772	61	200				
LH-SW150-035	1-3/8	35	48	1.890	61	200				
LH-SW150-038	1-1/2	38	51	2.008	61	200				
LH-SW150-045	1-3/4	45	59	2.323	61	200				
LH-SW150-051	2	51	65	2.559	61	200				
LH-SW150-063	2-1/2	63	80	3.150	61	200				
LH-SW150-076	3	76	94	3.701	61	200				
LH-SW150-080	3-3/16	80	98	3.858	61	200				
LH-SW150-090	3-1/2	90	108	4.252	61	200				
LH-SW150-102	4	102	120	4.724	61	200				
LH-SW150-127	5	127	145	5.709	30.5	100				
LH-SW150-152	6	152	171	6.732	30.5	100				
LH-SW150-203	8	203	223	8.780	15	50				
LH-SW150-254	10	254	275	10.807	15	50				
LH-SW150-305	12	305	325	12.795	15	50				

