

SW300 - Water Suction Hose



Application: It handles sewage, waste water or non corrosive liquid etc.

Temperature: -40°C~+85°C

Inner tube: Black smooth synthetic rubber

Reinforcement: High tensile cord and helix steel wire

Cover: Black, ozone, aging and abrasion resistant rubber compound

Part. No	Hose I.D.		Hose O.D		Max.Length		Working Pressure		Min Burst Pressure	
	in	mm	mm	in	m	ft	bar	psi	psi	psi
LH-SW300-025	1	25	38	1.496	61	200	20	300	60	900
LH-SW300-032	1-1/4	32	47	1.850	61	200				
LH-SW300-035	1-3/8	35	50	1.969	61	200				
LH-SW300-038	1-1/2	38	53	2.087	61	200				
LH-SW300-045	1-3/4	45	60	2.362	61	200				
LH-SW300-051	2	51	66	2.598	61	200				
LH-SW300-063	2-1/2	63	81	3.189	61	200				
LH-SW300-076	3	76	95	3.740	61	200				
LH-SW300-080	3-3/16	80	99	3.898	61	200				
LH-SW300-090	3-1/2	90	110	4.331	61	200				
LH-SW300-102	4	102	122	4.803	61	200				
LH-SW300-127	5	127	148	5.827	30.5	100				
LH-SW300-152	6	152	175	6.890	30.5	100				

