



## PVC FIBER REINFORCED HOSE

**Application:** It used for convey water and draining for equipment.

**Feature:**

- \* LIGHT DUTY.
- \* Passed the ROHS, PAHS test.
- \* Light, soft and easy for moving.
- \* Suitable for usual pressure environment.
- \* Beautiful surface and high quality.
- \* Anti-erosion, anti-uv.

Part Number	Type	Dimension		Length	Max.W.P	Max.B.P	Weight
		ID.mm	O.D.mm				
L-LPFRH0156	5/32"	4	8	100	10	50	49
L-LPFRH0203	13/64"	5	9	100	10	30	57
L-LPFRH0250	1/4"	6	10	100	10	40	65
L-LPFRH0313	5/16"	8	12	100	10	40	82
L-LPFRH0375	3/8"	10	14	100	9	35	98
L-LPFRH0501	1/2"	12	16	50	7	20	115
L-LPFRH0502	1/2"	12	17	50	8	24	150
L-LPFRH0503	1/2"	13	17	50	7	20	125
L-LPFRH06251	5/8"	15	19	50	6	20	140
L-LPFRH06252	5/8"	16	20	50	6	20	150
L-LPFRH06253	5/8"	16	21	50	7	21	190
L-LPFRH0751	3/4"	19	23	50	4	12	170
L-LPFRH0752	3/4"	19	24	50	4	12	220
L-LPFRH0753	3/4"	20	24	50	4	12	180
L-LPFRH0875	7/8"	22	27	50	3	12	250
L-LPFRH1001	1"	25	29	50	4	9	220
L-LPFRH1002	1"	25	30	50	3	12	281
L-LPFRH1250	1 1/4"	32	38	40	3	10	430
L-LPFRH1500	1 1/2"	38	45	40	3	10	590
L-LPFRH1750	1 3/4"	45	55	30	3	10	1020
L-LPFRH2000	2"	50	59	30	3	10	1010



## PVC FIBER REINFORCED HOSE

**Application:** It used for convey water and draining for equipment.

**Feature:**

- \* HEAVY DUTY.
- \* Passed the ROHS, PAHS test.
- \* Light, soft and easy for moving.
- \* Suitable for usual pressure environment.
- \* Beautiful surface and high quality.
- \* Anti-erosion, anti-uv.

Part Number	Type	Dimension		Length	Max.W.P	Max.B.P	Weight
		ID.mm	O.D.mm				
L-HPFRH0203	13/64"	5	10	100	12	40	76
L-HPFRH0250	1/4"	6	11	100	12	36	87
L-HPFRH0313	5/16"	8	13	100	10	30	105
L-HPFRH0375	3/8"	10	15	100	10	30	130
L-HPFRH0500	1/2"	12	18	100	9	27	185
L-HPFRH0625	5/8"	16	22	50	8	24	230
L-HPFRH0750	3/4"	19	25	50	6	18	270
L-HPFRH0875	7/8"	22	28	50	5	15	305
L-HPFRH1000	1"	25	31	50	5	15	340
L-HPFRH1250	1 1/4"	32	40	40	4	12	590
L-HPFRH1500	1 1/2"	38	46	40	4	12	690
L-HPFRH1750	1 3/4"	45	56	30	4	12	1140
L-HPFRH2000	2"	50	62	30	4	12	1380
L-HPFRH2500	2 1/2"	64	78	20	4	12	2030
L-HPFRH3000	3"	76	92	20	4	12	2750